We claim:

1.   A hearing aid, comprising:

a microphone to receive an input signal;

5   a speaker to reproduce the input signal; and

a processor to process the input signal at a gain, wherein the processor

includes an inhibitor to inhibit distortions and an adjuster to adjust the gain of the

input signal, wherein the inhibitor smoothes an envelope of the input signal so as

to inhibit distortions arising from apparent modulation of the input signal.

10

2.   The hearing aid of claim 1, wherein the inhibitor creates two

representations that are orthogonal to each other in phase.

3.   The hearing aid of claim 1, wherein the inhibitor includes a multiple of

15   time-constant circuits to smooth the envelope of the input signal.

4.   The hearing aid of claim 1, wherein the inhibitor includes a detector having

a Hilbert filter so as to smooth the envelope of the input signal.

20   5.   The hearing aid of claim 1, wherein the inhibitor includes an estimator that

estimates at least one of a minimum and a maximum of two representations of the

input signal that are orthogonal to each other in phase, wherein the estimator

allows a linear extraction of the amplitude so as to smooth the envelope of the

input signal.

5   6.   A method for providing automatic gain control, comprising:

smoothing an envelope of an input signal having a gain; and

adjusting the gain if the envelope is one of two conditions, wherein the two

conditions includes being greater than a threshold and being less than the

threshold, wherein the act of smoothing inhibits distortions arising from

10   modulation of the input signal.

7.   The method of claim 6, wherein smoothing includes creating two

representations of the input signal, wherein the two representations are orthogonal

to each other in phase.

15

8.   The method of claim 7, wherein creating includes creating the magnitude

of the two representations to approximate the magnitude of the input signal.

9.   The method of claim 7, wherein smoothing includes smoothing using a

20   Hilbert filter.

10. The method of claim 9, wherein smoothing includes squaring each sample to form a squared sample, summing each squared sample with other squared samples to form a sum, and taking a square root of the sum.

5   11. A hearing aid, comprising:

an adjuster to adjust a gain so as to amplify an input signal; and

a detector to form a smooth envelope that is a rectified version of the input signal, wherein the detector presents the smooth envelope to the adjuster, and wherein the smooth envelope excludes apparent modulation of the input signal.

10

12. The hearing aid of claim 11, further comprising a preamplifier having a gain to amplify the input signal, wherein the adjuster adjusts the gain of the preamplifier.

15   13. The hearing aid of claim 12, further comprising an analog-to-digital converter that receives the input signal, which is amplified by the preamplifier, and produces a digitized input signal.

14. The hearing aid of claim 13, further comprising a filter to receive the

20   digitized input signal and to produce a filtered input signal that excludes a direct-current component of the digitized input signal.

15.   The hearing aid of claim 14, further comprising a digital-to-analog

converter that receives a digital adjustment from the adjuster, produces an analog

adjustment, and presents the analog adjustment to the preamplifier.

5

16.   A hearing aid, comprising:

a preamplifier having a gain to amplify the input signal;

a detector to form a smooth envelope that is rectified; and

an adjuster to adjust the gain of the preamplifier if the smooth envelope is

10   one of two conditions, wherein the two conditions includes being greater than a

threshold and being less than the threshold, and wherein the smooth envelope is

defined to exclude the modulation that distorts the input signal.

17.   The hearing aid of claim 16, further comprising a filter to produce a

15   filtered input signal that excludes direct current.

18.   The hearing aid of claim 17, wherein the detector includes a Hilbert filter,

wherein the Hilbert filter receives the filtered input signal, and produces two

signals that are 90 degrees out of phase with each other.

20

19.   The hearing aid of claim 18, wherein the detector squares each signal of

the two signals, sums the two squared signals to form a sum, and takes the square

root of the sum to form the smooth envelope of the input signal.

20. The hearing aid of claim 18, wherein the detector squares each signal of

5 the two signals and sums the two squared signals to form the smooth envelope of

the input signal.

21. A digital analog gain control, comprising:

a detector to detect an envelope of an input signal using Hilbert filters;

10 an adder to provide a difference between the envelope and a threshold; and

an adjuster that adjust a gain if the difference is one of two conditions,

wherein the two conditions includes being greater than zero and being less than

zero.

15 22. The digital analog gain control of claim 21, further comprising a filter that

removes low frequencies, wherein the filter receives the input signal, removes

frequencies less than about 100 Hertz from the input signal, and presents the input

signal to the detector.

20 23. The digital analog gain control of claim 22, further comprising a digital

delay element that receives the input signal and presents a delayed input signal.

24.   The digital analog gain control of claim 23, further comprising a first

Hilbert filter and a second Hilbert filter, wherein the first Hilbert filter receives

the delayed input signal and filters the delayed input signal to form the first

5   filtered input signal, and wherein the second Hilbert filter receives the input signal

and filters the input signal to form the second filtered input signal.

25.   The digital analog gain control of claim 24, further comprising a first

multiplier and a second multiplier, wherein the first multiplier receives the first

10   filtered input signal and squares the first filtered input signal to form a first

squared signal, and wherein the second multiplier receives the second filtered

input signal and squares the second filtered input signal to form a second squared

signal.

15   26.   The digital analog gain control of claim 25, further comprising another

adder to add the first squared signal and the second squared signal to form a sum-

of-square signal.

27.   The digital analog gain control of claim 26, further comprising a limiter

20   that receives the sum-of-square signal, limits the sum-of-square signal to a desired

range, and presents a limited signal to the adder that provides the difference

between the envelope and the threshold.

28. A digital analog gain control, comprising:

a detector to detect an envelope of an input signal using Hilbert filters;

5   an adder to provide a difference between the envelope and a threshold; and

an adjuster that receives the difference, a release time constant, and an

attack time constant, wherein the adjuster adjust a gain if the difference is one of

two conditions, wherein the two conditions includes being a negative number and

being a positive number, wherein the adjuster increases the gain if the difference is

10   negative, and wherein the adjuster decreases the gain if the difference is positive.

29. The digital analog gain control of claim 28, wherein the adjuster receives a

previous gain, wherein if the difference is negative, the adjuster increases the gain

by shifting the bits of the previous gain to the right by the release time constant to

15   form a new gain and taking the negative of the new gain.

30. The digital analog gain control of claim 29, wherein if the difference is

positive, the adjuster decreases the gain by shifting the bits of the difference to the

right by the attack time constant to form the new gain.

20

31. The digital analog gain control of claim 30, further comprising a width

adjuster that adjusts the word with of the previous gain and presents an adjusted

previous gain.

32.   The digital analog gain control of claim 31, further comprising another

5   adder that adds the new gain and the adjusted previous gain to form the gain.

33.   The digital analog gain control of claim 32, further comprising a limiter to

the limit the range of the gain so that the gain is positive.

10   34.   The digital analog gain control of claim 33, further comprising a buffer

that stores the gain and presents the stored gain, wherein the stored gain is defined

as the previous gain, which is presented to the adjuster and the width adjuster.

35.   The digital analog gain control of claim 34, further comprising a rounding

15   circuit that rounds the stored gain to a smaller precision value so as to be

compatible with the input width of subsequent circuitry that includes a digital-to-

analog converter.

36.   A digital analog gain control, comprising:

20   a filter to block low frequencies from an input signal;

                a detector to detect an envelope of the input signal using Hilbert filters;

an adder to provide a difference between the envelope and a threshold; and

an adjuster that receives the difference, a release time constant, and an

attack time constant, wherein the adjuster adjust a gain if the difference is one of

two conditions, wherein the two conditions includes being a negative number and

5   being a positive number, wherein the adjuster increases the gain if the difference is

negative, and wherein the adjuster decreases the gain if the difference is positive.

37.   The digital analog gain control of claim 36, wherein the filter includes a

first digital delay that receives the input signal and presents a delayed input signal.

10

38.   The digital analog gain control of claim 37, wherein the filter includes a

first adder that determines a difference between the input signal and the delayed

input signal.

15   39.   The digital analog gain control of claim 38, wherein the filter includes a

first multiplier that multiplies the difference and a scale to form a scaled signal,

wherein the scaled signal inhibits the filter from overflow.

40.   The digital analog gain control of claim 39, wherein the filter includes a

20   second adder that adds the scaled signal and a blocked signal to form a filtered

signal.

41.   The digital analog gain control of claim 40, wherein the filter includes a

second digital delay that receives the filtered signal and presents a filtered signal

that is delayed.

5

42.   The digital analog gain control of claim 41, wherein the filter includes a

second multiplier that multiplies the filtered signal that is delayed and an alpha

signal to form a blocked signal, wherein the alpha signal determines a range of

frequencies that will be blocked by the filter.

10

43.   A digital analog gain control, comprising:

a detector to detect an envelope of the input signal using IIR filters;

an adder to provide a difference between the envelope and a threshold; and

an adjuster that receives the difference, a release time constant, and an

15   attack time constant, wherein the adjuster adjust a gain if the difference is one of

two conditions, wherein the two conditions includes being a negative number and

being a positive number, wherein the adjuster increases the gain if the difference is

negative, and wherein the adjuster decreases the gain if the difference is positive.

20   44.   The digital analog gain control of claim 43, wherein the IIR filters are

defined to be infinite-impulse-response filters.

45.   The digital analog gain control of claim 44, wherein each infinite-impulse-response filter includes a first delay, a second delay, and a scale element, wherein the input signal is delayed by the first delay, delayed by the second delay, and

5   scaled by the scale element to form a scaled signal.

46.   The digital analog gain control of claim 45, wherein each infinite-impulse response filter includes a first adder that determines a difference between the input signal and a feedback signal.

10

47.   The digital analog gain control of claim 46, wherein each infinite-impulse-response filter includes a multiplier that multiplies the difference and a beta signal to form a modified signal, wherein the beta signal modifies the phase of the difference.

15

48.   The digital analog gain control of claim 47, wherein each infinite-impulse-response filter includes a third delay that delays the modified signal to form a filtered signal.

20   49.   The digital analog gain control of claim 48, wherein each infinite-impulse-response filter includes a fourth delay that delays the filtered signal to form the

feedback signal.

50. A method for controlling a gain of an amplifier, comprising:

blocking low frequencies from an input signal that is digitized;

5 forming an envelope that lacks modulation using Hilbert filters; and

subtracting the envelope from a threshold to form a difference, wherein the

difference is used to control the gain.

51. The method of claim 50, wherein blocking includes blocking low

10 frequencies that are less than about 100 Hertz.

52. The method of claim 50, further comprising determining if the difference is

greater than zero.

15 53. The method of claim 52, further comprising shifting the bits of the

difference to the right by an attack constant to form a decreased gain.

54. The method of claim 53, further comprising shifting the bits of a negated

signal to the right by a release constant to form an increased gain.

20

55. The method of claim 54, further comprising switching for presenting the

decreased gain as the gain if the difference is greater than zero, or else the act of

switching presents the increased gain as the gain if the difference is less than zero.

56.   The method of claim 55, further comprising summing the gain and the

5   feedback signal that is delayed to form a modified gain signal.

57.   The method of claim 56, further comprising presenting a final gain to an

analog-to-digital converter, wherein the final gain is zero if the modified gain

signal is less than or equal to zero, and wherein the final gain is one if the

10   modified gain signal is greater than one.

58.   The method of claim 57, further comprising delaying the final gain to

produce the feedback signal that is delayed.

15   59.   The method of claim 58, further comprising negating the feedback signal

that is delayed to form the negated signal.

20